



# Selectarc Goug

*Chamfering Electrode*

## Classification

Without

## Description & Applications

Electrode for chamfering, grooving and gouging all metals, including stainless steels, cast iron and Cu alloys. Strong blowing characteristic to remove metal with high efficiency, smooth and uniform cut. Non-conductive coating. Surface becomes carbonised, therefore remove 0,1 mm by grinding if necessary.

Elimination of screws, rivets, welding beads, ...  
Chamfering of foundry defects or cracks before repair welding.  
Chamfering of hardfacing deposits or tempered steels.

## Welding Current & Instructions

Electrode	ØxL ( mm )	3,2x350	4,0x450
Current	( A )	200	250

Select the amperage depending on the diameter of the electrode. Hold the electrode at an angle of approx. 20°, push in direction of travel using a sa w like (forward and back) motion. Incline the workpiece, if possible, to favour the molten metal to flow away.

ind.13



= +	~ 55V
-----	-------

**Liability:** This document is intended to assist the user in choosing the product. It is up to the user to verify that the chosen product is suitable for applications for which it is intended. The company FSH Welding Group reserves the right to alter specifications without prior notice of its products. The descriptions, illustrations and specifications are for reference only and cannot be held liable for FSH Welding Group. **Fumes:** Consult information on MSDS, available upon request.